



THE
Water
Research
FOUNDATION

How Long is Too Long? Evaluating Extended Biofilter Shutdown WRF #4984

Eugene Water and Electric Board

Toby Dixon, Jared Giacomelli, Lonny Sayles, Ray Leipold

University of Toronto


Michael McKie, Robert Andrews

Water Research Foundation

Stephanie Fevig, Michael Dirks



Hayden Bridge Filtration Plant



Hayden Bridge Filtration Plant




Hayden Bridge Filtration Plant

- Conventional treatment plant
- Maximum capacity 88 MGD (400 MLD)
 - Typical production <44 MGD (200 MLD)
- Use 5 to 7 of the 14 filters to meet demand
 - Filters placed out of service after backwash to cycle through all filters
 - Shutdown for 3 to 5 days during warm-water periods (>10°C)
 - Shutdown up to 7 days during cold-water periods (<10°C)
 - Filter to waste prior to production to meet turbidity target



Hayden Bridge Filtration Plant



EWEB Drivers for Research

- Cost certainty and risk reduction
 - Reliance on few chlorine gas suppliers on the west coast
- Operational resiliency and flexibility
 - On-site sodium hypochlorite production facility planned
 - Emphasized the need for process optimization
- Give operators confidence with the new treatment approach
 - A culture of continuous improvement and understanding



WRF 4984 Objectives

- What happens when pre-chlorination stops?
- Is filter shutdown a viable operating strategy moving forward?
- How can plant operation be “optimized”?



PROJECT NO.
4984




Impact of Intermittent Operation on Biofilter Performance



What is Biofiltration?

- Filters operated with limited exposure to oxidants
 - Preferably no exposure
- Naturally occurring bacteria attach and form a biofilm layer
- Bacteria degrade, oxidize or consume various substrates




Anticipated Benefits of Biofiltration

- Improved removal of organics
- Nutrient sequestration
- More “biostable” treated water
 - Lower regrowth potential
- Taste and odour control
 - Geosmin and MIB
- Reduced chemical usage
 - Pre-treatment and disinfectants



HBFP Pilot Facility



HBFP Pilot Facility



Control and Chlorinated Pilot Filters



Experimental Pilot Filter


Parameters of Interest

- Organics
 - Dissolved organic carbon, UV_{254} , THM and HAA Formation potential
- Inorganic nutrients
 - Nitrate, Nitrite, Ammonia, Phosphorus
- Biological characterization
 - ATP, enzyme activity
- Other parameters
 - Dissolved oxygen uptake, pH, filter run time, unit filter run volume


1) What Happens When Pre-chlorination Stops?

- Experimental filter commissioned in December 2018
 - Anthracite and sand from the full-scale filters
 - Operated continuously to mimic control filter
 - Control and chlorinated pilot filters in operation for many years prior
- Evaluation of filter acclimation included:
 - Biomass development (via ATP)
 - Biofilm activity (via enzyme activity)
- Trial conducted under worst-case conditions (cold-water <10°C)

Biomass Development



Biological Activity



Impacts of Stopping Pre-chlorination

- Filters became biologically active
- Similar amount of biomass after 3 to 4 months
 - Cold water may have slowed growth
- Biological activity was equivalent within 1 month
 - May be a better indicator of acclimation
- Filtered water quality was similar to the control
- Successful “proof of concept”

2) Evaluating the Impact of Biofilter Shutdown


- Microorganisms need nutrients to survive
 - Carbon, oxygen, trace minerals, etc.
- Filter shutdown limits the exposure to those nutrients
- Problem statement: What is the longest a filter could be shutdown and remain biological while achieving acceptable water quality?

Warm-water (>10°C) Shutdown Testing

- Evaluate filter performance with shutdowns from 2 to 48 hours
 - Each condition evaluated for 2 weeks
- Samples collected weekly and shipped to the U of T laboratory
 - Huge amount of coordination required
- Unit filter run volume to assess production




Enzyme Activity - Esterase




Summary of Biomass Characterization

- Similar ATP *trend* observed between control and experimental filters
 - Potentially related to changes in substrate (e.g. carbon)
 - Relatively lower experimental ATP may be due to less mature biofilm
- Esterase activity elevated with extended filter shutdowns
 - Relatively more active biomass
- No relationship to temperature observed

Organics Removal - DOC




Organics Removal – THM FP



Summary of Water Quality Monitoring

- All filters achieved similar levels of organics removal
 - Likely limited removal achieved biologically – still achieves objective!
- Common biofiltration monitoring parameters (pH, DO uptake, UV₂₅₄) are poor indicators of performance at this location
- Filter shutdown duration did not affect performance
 - No changes to operation evident

Filter Production




Major Project Findings

- Eliminating pre-chlorination resulted in biologically active filters
 - No changes in filtered water quality anticipated
- Filters without pre-chlorination had higher production capacities as measured by UFRV
 - Extended shutdown following backwash improved this further
- Full-scale elimination of pre-chlorination was a viable approach

Next Steps – GAC Caps

- 6” caps added to experimental filter
 - Corresponds to media depth added to alleviate existing media attrition
- Project objectives included:
 - Removal of organics (DOC, DBPs, etc)
 - Chlorine demand
 - Control of cyanotoxin surrogates
- Justify anthracite replacement with GAC
 - Cost-benefit analysis

Organics Removal



Crowe, G.T., Almuhtaram, H., Andrews, R.C. & McKie, M.J. 2022. Granular Activated Carbon Caps – A Potential Treatment Barrier for Drinking Water Cyanotoxins. *Journal of Water Process Engineering*, 49. <https://doi.org/10.1016/j.jwpe.2022.102977>

Thank you!

Michael McKie, Ph.D., P.Eng.

Project Engineer, ClMA+

Michael.McKie@cima.ca

519-501-9122

