

Agenda

01 02 03 04
Who are we? Nosedo WWTP, Milan, Italy Challenges Results

04 05 06 07

Solution Main control strategies GHG savings Additional potential



VEOLIA HUBGRADE PERFORMANCE PLANT KEY TAKE-AWAYS

- NEW WINDOW TO PLANNING CAPITAL UPGRADES
- OPTIMIZES EXISTING ASSETS



- OVER 100 REFERENCES WW
- PROVEN IN PRACTICE



- VEOLIA PROCESS EXPERTISE
- FIRST IN CLASS PARTNERS
- OPERATOR REMAINS IN CONTROL



Veolia Water Technologies Canada



- Veolia Environnement group
- \$63B CAD 2022 revenues
- Water, waste, energy
- 75 years in Canada





NOSEDO WWTP (MILAN), ITALY IMPROVEMENTS REQUIRED AFTER 15 YEARS








NOSEDO WWTP (MILAN), ITALY 1.25M PE - MLE






Challenges

- 1. Reduce operational costs
- 2. Improve wet weather handling
- 3. Improve biological load variations handling

HUBGRADE PERFORMANCE PLANT REAL TIME OPTIMISATION AS A SERVICE



Strategy

Own Calculation AND Digital Twin SetPoint
Operator remains in control

Optimization

24/7/365 / Holistic / Best possible outcome Handles multiple sets of Data

REAL TIME OPTIMISATION AS A SERVICE TO ANSWER VARIOUS NEEDS

Compliance



Ensure high level of water quality to comply with stringent regulations - 24/7-365

Operational excellence



Reduce OPEX, avoid investments and increase

productive **uptime**

Sustainability



Reduce your environmental footprint

Achieve sustainable development goals

BACK TO NOSEDO - PERFORMANCE GUARANTEE () **RESULTS OVER EXPECTATIONS & ROI < 2 YEARS**





Compliance

Contractual

- Total N < **10** mg/l
- Total P < 1 mg/l

Achieved*

- Total N: From 7.1 to 4.6 mg/l
- Total P: From **0.90** to **0.84** mg/l

10 to 30% reduction

Operational excellence

Contractual

• Reduce Electricity & Coagulant OPEX by 400k€ / year

Achieved*

• Reduce Electricity & Coagulant OPEX by **740k€** / year

Reality**: 1,967k€ in 2023

85% more than expected





- 60%

Sustainability

Contractual


• No requirement on reduction in CO2 equivalent

Achieved*

- 1.5k t/v CO2 (elec & chemicals)
- 20k t CO2 (BioP tank avoided)


25 000 tonnes of CO2 avoided

HOW DID WE OBTAIN SUCH RESULTS? FEATURES AS A SERVICE - MORE THAN 50 FEATURES



DO & Nitrogen Removal - Al Based on Model Predictive Control (MPC)


- **1. Implement a model** switch predicts the future based on the history incl. time delays in sensors, equipment, biomass and loading
- **1. Optimize** and "choose" the best optimization from a number of criterias
- **1. Update automatically** the predictions and optimisation each 2. minutes as soon as new data/information are available





HUBGRADE + SENSORS + EQUIPMENTS 1M € PROJECT - 1 YEAR TO SET IT UP





ENHANCED ABAC - DO & N REMOVAL BASED ON NH₄, NO₃ AND POSSIBLY PO₄















DO & Nitrogen Removal

WHY

- Ensure compliance
- Reduce OPEX (energy)
- Reduce CO₂ emissions
- Lower SVI (Easier sludge settling)

HOW


- Avoid over-aeration
- Enhance the usage of COD for NO₃ removal.
- Enhance balancing of N/DN processes according to load variations.


WHAT

Two patented optimized controls:

- regulating the DO set point
- o regulating N/DN switching phases.

Providing set points for intermittent aeration and DO based on real-time measurements of NH₄. NO₃ and PO₄ in the aeration tanks.





STANDBY® MODULE












OPTIMIZE DURING LOW LOADS OR GOOD PERFORMANCE

WHAT WHY HOW Patented real-time optimization: Reduce OPEX (energy) Temporary standby/close down Reduce coagulant due to process lines when low load/good **Standby** Providing set points for relevant Enhanced Bio-P performance has been detected standby of 1 or many lines by stopping Enhanced biomass Let biomass go anaerobic and inlet, mixer, aeration, internal pumping remove P




SMART BIO-P® ENHANCED BIO-P IN EXISTING N/DN TANKS




Capacity

Compliance








SMART BIO-P® - ENHANCED BIO-P IN N/DN TANKS REDUCE COAGULANT DOSAGE





STORMWATER MODE® **FEATURE IN DETAIL**

















Stormwater Mode

Increase flow through biological WWTP during rain events

WHY



HOW

 Real time control of settling phases to keep activated sludge inside the process tanks during highflow

WHAT

Find a place for settling of activated sludge somewhere in existing volume

Adaptable to all activated sludge plant designs

Example: Conventional plugflow ASP - MLE Settling in selected sections N/DN in other sections Anoxic -> Aerobic Aerobic/Anoxic -> (Aerobic or settling) /Anoxic Settling 2 - 3 g/L to 3-4 g/L 4 g/L 4 g/L

STORMWATER MODE® - BETTER HANDLING OF RAIN PREPARE FOR RAIN (SETTLING, FORCED RAS FLOW, CLEANING...)





Minimise internal pumping to improve settling Balance sludge level between settling tanks

BACK TO NOSEDO () **APPLIED MODULES**

DO & Nitrogen Removal (A) **SMARTGrid Spot Price**





Footprint




Main Benefits*:

- Energy consumption is balanced & postponed to lower price period.
- 10 to 20 % more OPEX savings 400 k€/y (600 k\$CAD/y)

Extra CAPEX:

Nothing needed (apart Hubgrade;))



Main Benefits*:

Minimize N₂O emissions by up to 80% balancing the N / DN periods based on N₂O measures

N₂O-minimization

Extra CAPEX:

Additional N₂O sensors



Main Benefits*:


Usage of unused volumes in the system (pipes and/or basins in the sewer & wwtp network) as storage volume(s)

Dry Weather Equalization

15 to 30% more OPEX savings 650 k€/y (1000 k\$CAD/y)

Extra CAPEX:

Hydraulic sewer pre- study + potential mechanical automations



*: Compliance is always the priority



VEOLIA HUBGRADE PERFORMANCE PLANT KEY TAKE-AWAYS

- NEW WINDOW TO PLANNING CAPITAL UPGRADES
- OPTIMIZES EXISTING ASSETS



- OVER 100 REFERENCES WW
- PROVEN IN PRACTICE



- VEOLIA PROCESS EXPERTISE
- FIRST IN CLASS PARTNERS
- OPERATOR REMAINS IN CONTROL



THANKS - Questions?

Contact Information:

David.pearce@veolia.com

416-768-8158